



ENERGY STORAGE BATTERY

-Rack Mounted Type

- Easy Operation and installation
- Flexible Expansion in parallel
- Compatibility with many inverter brands
- Wake up by voltage or communication
- Low self-consumption for storage or long rainy days
- High safety level with automotive LFP cell and function safety design
- Fire fighting device inside battery
- High peak current to start the inductive load



SPECIFICATION

Model	RE-L-5.0-X03
Battery Chemistry	Lithium Iron Phosphate (LiFePO4)
Cell string	15S
Nominal Voltage	48V
Battery capacity	105Ah
Nominal Energy	5.04KWh
Usable Energy	4.54KWh
Operating Voltage Range	37.5V-54V
Recommended Charge/Discharge Current	50A
Max. Charge/Discharge Current (Peak)	100A
Dimension (W*D*H)	442*150*480 mm(exclude handle)
Weight(Kg)	45Kg
Operating Temperature Range	Charge: 0°C ~ +45°C
	Discharge: -20°C ~ +55°C
Recommended Operating Environment	+15 ~ +35°C
Storage Temperature	-20 ~ +45°C
Humidity	5%~95%
Altitude (m)	<2000
Design Life	10+Years
Cycle Life	>6000cycles,@0.5C @25°C DOD 80%
Certifications	IEC62619/CE/UN38.3
Module Parallel	Up to 8 Units
Months Self Discharge	<1%
SOC Display	LED indicator light
Communication (Optional)	CAN/RS485

PHYLION BATTERY CO., LTD.
 PHYLION BATTERY (NL) B.V.
 Web: www.phylion.com

Add: Suzhou, Jiangsu, China
 Add: Wierden, The Netherlands
 E-mail: info.ess@phylion.com